# ROOPAM STEEL

NO SUBSTITUTE FOR TRUST

ISO 9001: 2015 | ISO 14001: 2015 | ISO 45001: 2018

**Head Office:**
96, Nanubhai Desai Road, Mumbai, Maharashtra, India

**Pipes and Tubes Manufacturing Plant:**
GIDC Manjusar, Vadodara, Gujarat, India

**Pipe Fittings and Flanges Plant:**
Taloja, Maharashtra, India

For more details visit: **www.roopamsteel.com**

## PIPE DIMENSIONS AND WEIGHTS

U.S./METRIC

| NOMINAL PIPE SIZE | OD | SCHEDULE DESIGNATIONS | | | WALL THICKNESS | | WEIGHT | | ID | |
|---|---|---|---|---|---|---|---|---|---|---|
| INCH MM | INCH MM | ASME | | | INCH | MM | LBS/ FOOT | KG/ METER | INCH | MM |
| 1/8<br>6 | 0.405<br>10.3 | 10<br>STD<br>XS | 40<br>80 | 10S<br>40S<br>80S | 0.049<br>0.068<br>0.095 | 1.24<br>1.73<br>2.41 | 0.19<br>0.24<br>0.31 | 0.28<br>0.37<br>0.47 | 0.307<br>0.269<br>0.215 | 7.82<br>6.84<br>5.84 |
| 1/4<br>8 | 0.540<br>13.7 | 10<br>STD<br>XS | 40<br>80 | 10S<br>40S<br>80S | 0.065<br>0.088<br>0.119 | 1.65<br>2.24<br>3.02 | 0.33<br>0.43<br>0.54 | 0.49<br>0.63<br>0.80 | 0.410<br>0.364<br>0.302 | 10.40<br>9.22<br>7.66 |
| 3/8<br>10 | 0.675<br>17.1 | 10<br>STD<br>XS | 40<br>80 | 10S<br>40S<br>80S | 0.065<br>0.091<br>0.126 | 1.65<br>2.31<br>3.20 | 0.42<br>0.57<br>0.74 | 0.63<br>0.84<br>1.10 | 0.545<br>0.493<br>0.423 | 13.80<br>12.48<br>10.70 |
| 1/2<br>15 | 0.840<br>21.3 | 5<br>10<br>STD<br>XS<br>160<br>XX | 40<br>80 | 5S<br>10S<br>40S<br>80S | 0.065<br>0.083<br>0.109<br>0.147<br>0.188<br>0.294 | 1.65<br>2.11<br>2.77<br>3.73<br>4.78<br>7.47 | 0.54<br>0.67<br>0.85<br>1.09<br>1.31<br>1.72 | 0.80<br>1.00<br>1.27<br>1.62<br>1.95<br>2.55 | 0.710<br>0.674<br>0.622<br>0.546<br>0.464<br>0.252 | 18.00<br>17.08<br>15.76<br>13.84<br>11.74<br>6.36 |
| 3/4<br>20 | 1.050<br>26.7 | 5<br>10<br>STD<br>XS<br>160<br>XX | 40<br>80 | 5S<br>10S<br>40S<br>80S | 0.065<br>0.083<br>0.113<br>0.154<br>0.219<br>0.308 | 1.65<br>2.11<br>2.87<br>3.91<br>5.56<br>7.82 | 0.69<br>0.86<br>1.13<br>1.48<br>1.95<br>2.44 | 1.03<br>1.28<br>1.69<br>2.20<br>2.90<br>3.64 | 0.920<br>0.884<br>0.824<br>0.742<br>0.612<br>0.434 | 23.40<br>22.48<br>20.96<br>18.88<br>15.58<br>11.06 |
| 1<br>25 | 1.315<br>33.4 | 5<br>10<br>STD<br>XS<br>160<br>XX | 40<br>80 | 5S<br>10S<br>40S<br>80S | 0.065<br>0.109<br>0.133<br>0.179<br>0.250<br>0.358 | 1.65<br>2.77<br>3.38<br>4.55<br>6.35<br>9.09 | 0.87<br>1.41<br>1.68<br>2.17<br>2.85<br>3.66 | 1.29<br>2.09<br>2.50<br>3.24<br>4.24<br>5.45 | 1.185<br>1.097<br>1.049<br>0.957<br>0.815<br>0.599 | 30.10<br>27.86<br>26.64<br>24.30<br>20.70<br>15.22 |
| 1-1/4<br>32 | 1.660<br>42.2 | 5<br>10<br>STD<br>XS<br>160<br>XX | 40<br>80 | 5S<br>10S<br>40S<br>80S | 0.065<br>0.109<br>0.140<br>0.191<br>0.250<br>0.382 | 1.65<br>2.77<br>3.56<br>4.85<br>6.35<br>9.70 | 1.11<br>1.81<br>2.27<br>3.00<br>3.77<br>5.22 | 1.65<br>2.69<br>3.39<br>4.47<br>5.61<br>7.77 | 1.530<br>1.442<br>1.380<br>1.278<br>1.160<br>0.896 | 38.90<br>36.66<br>35.08<br>32.50<br>29.50<br>22.80 |
| 1-1/2<br>40 | 1.900<br>48.3 | 5<br>10<br>STD<br>XS<br>160<br>XX | 40<br>80 | 5S<br>10S<br>40S<br>80S | 0.065<br>0.109<br>0.145<br>0.200<br>0.281<br>0.400 | 1.65<br>2.77<br>3.68<br>5.08<br>7.14<br>10.15 | 1.28<br>2.09<br>2.72<br>3.63<br>4.86<br>6.41 | 1.90<br>3.11<br>4.05<br>5.41<br>7.25<br>9.55 | 1.770<br>1.682<br>1.610<br>1.500<br>1.338<br>1.100 | 45.00<br>42.76<br>40.94<br>38.14<br>34.02<br>28.00 |
| 2<br>50 | 2.375<br>60.3 | 5<br>10<br>STD<br>XS<br>160<br>XX | 40<br>80 | 5S<br>10S<br>40S<br>80S | 0.065<br>0.109<br>0.154<br>0.218<br>0.344<br>0.436 | 1.65<br>2.77<br>3.91<br>5.54<br>8.74<br>11.07 | 1.61<br>2.64<br>3.66<br>5.03<br>7.47<br>9.04 | 2.39<br>3.93<br>5.44<br>7.48<br>11.11<br>13.44 | 2.245<br>2.157<br>2.067<br>1.939<br>1.687<br>1.503 | 57.00<br>54.76<br>52.48<br>49.22<br>42.82<br>38.16 |
| 2-1/2<br>65 | 2.875<br>73.0 | 5<br>10<br>STD<br>XS<br>160<br>XX | 40<br>80 | 5S<br>10S<br>40S<br>80S | 0.083<br>0.120<br>0.203<br>0.276<br>0.375<br>0.552 | 2.11<br>3.05<br>5.16<br>7.01<br>9.53<br>14.02 | 2.48<br>3.53<br>5.80<br>7.67<br>10.02<br>13.71 | 3.69<br>5.26<br>8.63<br>11.41<br>14.92<br>20.39 | 2.709<br>2.635<br>2.469<br>2.323<br>2.125<br>1.771 | 68.78<br>66.90<br>62.68<br>58.98<br>53.94<br>44.96 |
| 3<br>80 | 3.500<br>88.9 | 5<br>10<br>STD<br>XS<br>160<br>XX | 40<br>80 | 5S<br>10S<br>40S<br>80S | 0.083<br>0.120<br>0.216<br>0.300<br>0.438<br>0.600 | 2.11<br>3.05<br>5.49<br>7.62<br>11.13<br>15.24 | 3.03<br>4.34<br>7.58<br>10.26<br>14.34<br>18.60 | 4.52<br>6.46<br>11.29<br>15.27<br>21.35<br>27.68 | 3.334<br>3.260<br>3.068<br>2.900<br>2.624<br>2.300 | 84.68<br>82.80<br>77.92<br>73.66<br>66.64<br>58.42 |
| 3-1/2<br>90 | 4.000<br>101.6 | 5<br>10<br>STD<br>XS<br>XX | 40<br>80 | 5S<br>10S<br>40S<br>80S | 0.083<br>0.120<br>0.226<br>0.318<br>0.636 | 2.11<br>3.05<br>5.74<br>8.08<br>16.15 | 3.48<br>4.98<br>9.12<br>12.52<br>22.87 | 5.18<br>7.41<br>13.57<br>18.64<br>34.03 | 3.834<br>3.760<br>3.548<br>3.364<br>2.728 | 97.38<br>95.50<br>90.12<br>85.44<br>69.30 |
| 4<br>100 | 4.500<br>114.3 | 5<br>10<br>STD<br>XS<br>120<br>160<br>XX | 40<br>80 | 5S<br>10S<br>40S<br>80S | 0.083<br>0.120<br>0.156<br>0.188<br>0.237<br>0.337<br>0.438<br>0.531<br>0.674 | 2.11<br>3.05<br>3.96<br>4.78<br>6.02<br>8.56<br>11.13<br>13.49<br>17.12 | 3.92<br>5.62<br>7.24<br>8.67<br>10.80<br>15.00<br>19.02<br>22.53<br>27.57 | 5.84<br>8.37<br>10.78<br>12.91<br>16.08<br>22.32<br>28.32<br>33.54<br>41.03 | 4.334<br>4.260<br>4.188<br>4.124<br>4.026<br>3.826<br>3.624<br>3.438<br>3.152 | 110.08<br>108.20<br>106.38<br>104.74<br>102.26<br>97.18<br>92.04<br>87.32<br>80.06 |
| 4-1/2<br>115 | 5.000<br>127.0 | STD<br>XS<br>XX | 40<br>80 | 40S<br>80S | 0.247<br>0.355<br>0.710 | 6.27<br>9.02<br>18.03 | 12.55<br>17.63<br>32.56 | 18.67<br>26.24<br>48.45 | 4.506<br>4.290<br>3.580 | 114.46<br>108.96<br>90.94 |

| NOMINAL PIPE SIZE | OD | SCHEDULE DESIGNATIONS | | | WALL THICKNESS | | WEIGHT | | ID | |
|---|---|---|---|---|---|---|---|---|---|---|
| INCH MM | INCH MM | ASME | | | INCH | MM | LBS/ FOOT | KG/ METER | INCH | MM |
| 5<br>125 | 5.563<br>141.3 | 5<br>10<br>STD<br>XS<br>120<br>160<br>XX | 40<br>80 | 5S<br>10S<br>40S<br>80S | 0.109<br>0.134<br>0.258<br>0.375<br>0.500<br>0.625<br>0.750 | 2.77<br>3.40<br>6.55<br>9.53<br>12.70<br>15.88<br>19.05 | 6.36<br>7.78<br>14.63<br>20.80<br>27.06<br>32.99<br>38.59 | 9.46<br>11.56<br>21.77<br>30.97<br>40.28<br>49.12<br>57.43 | 5.345<br>5.295<br>5.047<br>4.813<br>4.563<br>4.313<br>4.063 | 135.76<br>134.50<br>128.20<br>122.24<br>115.90<br>109.54<br>103.20 |
| 6<br>150 | 6.625<br>168.3 | 5<br>10<br><br>STD<br>XS<br>120<br>160<br>XX | 40<br>80 | 5S<br>10S<br><br>40S<br>80S | 0.109<br>0.134<br>0.188<br>0.280<br>0.432<br>0.562<br>0.719<br>0.864 | 2.77<br>3.40<br>4.78<br>7.11<br>10.97<br>14.27<br>18.26<br>21.95 | 7.59<br>9.30<br>12.94<br>18.99<br>28.60<br>36.43<br>45.39<br>53.21 | 11.31<br>13.83<br>19.28<br>28.26<br>42.56<br>54.21<br>67.57<br>79.22 | 6.407<br>6.357<br>6.249<br>6.065<br>5.761<br>5.501<br>5.187<br>4.897 | 162.76<br>161.50<br>158.74<br>154.08<br>146.36<br>139.76<br>131.78<br>124.40 |
| 7<br>175 | 7.625<br>193.7 | STD<br>XS<br>XX | 40<br>80 | 40S<br>80S | 0.301<br>0.500<br>0.875 | 7.65<br>12.70<br>22.23 | 23.57<br>38.08<br>63.14 | 35.10<br>56.69<br>94.00 | 7.023<br>6.625<br>5.875 | 178.40<br>168.30<br>149.24 |
| 8<br>200 | 8.625<br>219.1 | <br>10<br>20<br>30<br>STD<br>60<br>XS<br>100<br>120<br>140<br>XX<br>160 | <br><br><br><br>40<br><br>80<br><br><br><br><br> | 5S<br>10S<br><br><br>40S<br><br>80S<br><br><br><br><br> | 0.109<br>0.148<br>0.250<br>0.277<br>0.322<br>0.406<br>0.500<br>0.594<br>0.719<br>0.812<br>0.875<br>0.906 | 2.77<br>3.76<br>6.35<br>7.04<br>8.18<br>10.31<br>12.70<br>15.09<br>18.26<br>20.62<br>22.23<br>23.01 | 9.92<br>13.41<br>22.38<br>24.72<br>28.58<br>35.67<br>43.43<br>51.00<br>60.77<br>67.82<br>72.49<br>74.76 | 14.78<br>19.97<br>33.32<br>36.82<br>42.55<br>53.09<br>64.64<br>75.92<br>90.44<br>100.93<br>107.93<br>111.27 | 8.407<br>8.329<br>8.125<br>8.071<br>7.981<br>7.813<br>7.625<br>7.437<br>7.187<br>7.001<br>6.875<br>6.813 | 213.56<br>211.58<br>206.40<br>205.02<br>202.74<br>198.48<br>193.70<br>188.92<br>182.58<br>177.86<br>174.64<br>173.08 |
| 9<br>225 | 9.625<br>244.5 | STD<br>XS<br>XX | 40<br>80 | 40S<br>80S | 0.342<br>0.500<br>0.875 | 8.69<br>12.70<br>22.23 | 33.94<br>48.77<br>81.85 | 50.54<br>72.60<br>121.85 | 8.941<br>8.625<br>7.875 | 227.12<br>219.10<br>200.04 |
| 10<br>250 | 10.750<br>273.0 | <br><br><br>20<br>30<br>STD<br>XS<br>80<br>100<br>120<br>140<br>160 | <br><br><br><br><br>40<br>60<br><br><br><br>XX<br> | 5S<br>10S<br><br><br><br>40S<br>80S<br><br><br><br><br> | 0.134<br>0.165<br>0.188<br>0.250<br>0.307<br>0.365<br>0.500<br>0.594<br>0.719<br>0.844<br>1.000<br>1.125 | 3.40<br>4.19<br>4.78<br>6.35<br>7.80<br>9.27<br>12.70<br>15.09<br>18.26<br>21.44<br>25.40<br>28.58 | 15.21<br>18.67<br>21.23<br>28.06<br>34.27<br>40.52<br>54.79<br>64.49<br>77.10<br>89.38<br>104.23<br>115.75 | 22.61<br>27.78<br>31.62<br>41.76<br>51.01<br>60.29<br>81.53<br>95.98<br>114.71<br>133.01<br>155.10<br>172.27 | 10.482<br>10.420<br>10.374<br>10.250<br>10.136<br>10.020<br>9.750<br>9.562<br>9.312<br>9.062<br>8.750<br>8.500 | 266.20<br>264.62<br>263.44<br>260.30<br>257.40<br>254.46<br>247.60<br>242.82<br>236.48<br>230.12<br>222.20<br>215.84 |
| 11<br>275 | 11.750<br>298.5 | STD<br>XS<br>XX | 40<br>80 | 40S<br>80S | 0.375<br>0.500<br>0.875 | 9.53<br>12.70<br>22.23 | 45.60<br>60.13<br>101.72 | 67.91<br>89.51<br>151.46 | 11.000<br>10.750<br>10.000 | 279.44<br>273.10<br>254.04 |
| 12<br>300 | 12.750<br>323.8 | <br><br><br>20<br>30<br>STD<br>40<br>XS<br>60<br>80<br>100<br>120<br>140<br>160 | <br><br><br><br><br><br><br><br><br><br><br>XX<br> | 5S<br>10S<br><br><br><br>40S<br><br>80S<br><br><br><br><br> | 0.156<br>0.180<br>0.188<br>0.250<br>0.330<br>0.375<br>0.406<br>0.500<br>0.562<br>0.688<br>0.844<br>1.000<br>1.125<br>1.312 | 3.96<br>4.57<br>4.78<br>6.35<br>8.38<br>9.53<br>10.31<br>12.70<br>14.27<br>17.48<br>21.44<br>25.40<br>28.58<br>33.32 | 21.00<br>24.19<br>25.25<br>33.41<br>43.81<br>49.61<br>53.57<br>65.48<br>73.22<br>88.71<br>107.42<br>125.61<br>139.81<br>160.42 | 31.24<br>35.98<br>37.61<br>49.71<br>65.19<br>73.86<br>79.71<br>97.44<br>108.93<br>132.05<br>159.87<br>186.92<br>208.08<br>238.69 | 12.438<br>12.390<br>12.374<br>12.250<br>12.090<br>12.000<br>11.938<br>11.750<br>11.626<br>11.374<br>11.062<br>10.750<br>10.500<br>10.126 | 315.88<br>314.66<br>314.24<br>311.10<br>307.04<br>304.74<br>303.18<br>298.40<br>295.26<br>288.84<br>280.92<br>273.00<br>266.64<br>257.16 |
| 14<br>350 | 14.000<br>355.6 | <br>10<br>20<br>STD<br>40<br>XS<br>60<br>80<br>100<br>120<br>140<br>160 | <br><br><br>30<br><br><br><br><br><br><br><br> | 10S<br><br><br>40S<br><br>80S<br><br><br><br><br><br> | 0.188<br>0.250<br>0.312<br>0.375<br>0.438<br>0.500<br>0.594<br>0.750<br>0.938<br>1.094<br>1.250<br>1.406 | 4.78<br>6.35<br>7.92<br>9.53<br>11.13<br>12.70<br>15.09<br>19.05<br>23.83<br>27.79<br>31.75<br>35.71 | 27.76<br>36.75<br>45.65<br>54.62<br>63.50<br>72.16<br>85.13<br>106.23<br>130.98<br>150.93<br>170.37<br>189.29 | 41.36<br>54.69<br>67.91<br>81.33<br>94.55<br>107.40<br>126.72<br>158.11<br>194.98<br>224.66<br>253.58<br>281.72 | 13.624<br>13.500<br>13.376<br>13.250<br>13.124<br>13.000<br>12.812<br>12.500<br>12.124<br>11.812<br>11.500<br>11.188 | 346.04<br>342.90<br>339.76<br>336.54<br>333.34<br>330.20<br>325.42<br>317.50<br>307.94<br>300.02<br>292.10<br>284.18 |

**Contact us : (Mob) +91 80705 36660 | (Mob) +91 75060 90755 | export@roopamsteel.com | marketing@roopamsteel.com**

| NOMINAL PIPE SIZE | OD | SCHEDULE DESIGNATIONS | WALL THICKNESS | | WEIGHT | | ID | |
|---|---|---|---|---|---|---|---|---|
| INCH MM | INCH MM | ASME | INCH | MM | LBS/ FOOT | KG/ METER | INCH | MM |
| 16 400 | 16.000 406.4 | 10S | 0.188 | 4.78 | 31.78 | 47.34 | 15.624 | 396.84 |
| | | 10 | 0.250 | 6.35 | 42.09 | 62.65 | 15.500 | 393.70 |
| | | 20 | 0.312 | 7.92 | 52.32 | 77.83 | 15.376 | 390.56 |
| | | STD 30 40S | 0.375 | 9.53 | 62.64 | 93.27 | 15.250 | 387.34 |
| | | XS 40 80S | 0.500 | 12.70 | 82.85 | 123.31 | 15.000 | 381.00 |
| | | 60 | 0.656 | 16.66 | 107.60 | 160.13 | 14.688 | 373.08 |
| | | 80 | 0.844 | 21.44 | 136.74 | 203.54 | 14.312 | 363.52 |
| | | 100 | 1.031 | 26.19 | 164.98 | 245.57 | 13.938 | 354.02 |
| | | 120 | 1.219 | 30.96 | 192.61 | 286.66 | 13.562 | 344.48 |
| | | 140 | 1.438 | 36.53 | 223.85 | 333.21 | 13.124 | 333.34 |
| | | 160 | 1.594 | 40.49 | 245.48 | 365.38 | 12.812 | 325.42 |
| 18 450 | 18.000 457 | 10S | 0.188 | 4.78 | 35.80 | 53.31 | 17.624 | 447.44 |
| | | 10 | 0.250 | 6.35 | 47.44 | 70.57 | 17.500 | 444.30 |
| | | 20 | 0.312 | 7.92 | 58.99 | 87.71 | 17.376 | 441.16 |
| | | STD 40S | 0.375 | 9.53 | 70.65 | 105.17 | 17.250 | 437.94 |
| | | 30 | 0.438 | 11.13 | 82.23 | 122.38 | 17.124 | 434.74 |
| | | XS 80S | 0.500 | 12.70 | 93.54 | 139.16 | 17.000 | 431.60 |
| | | 40 | 0.562 | 14.27 | 104.76 | 155.81 | 16.876 | 428.46 |
| | | 60 | 0.750 | 19.05 | 138.30 | 205.75 | 16.500 | 418.90 |
| | | 80 | 0.938 | 23.83 | 171.08 | 254.57 | 16.124 | 409.34 |
| | | 100 | 1.156 | 29.36 | 208.15 | 309.64 | 15.688 | 398.28 |
| | | 120 | 1.375 | 34.93 | 244.37 | 363.58 | 15.250 | 387.14 |
| | | 140 | 1.562 | 39.67 | 274.48 | 408.28 | 14.876 | 377.66 |
| | | 160 | 1.781 | 45.24 | 308.79 | 459.39 | 14.438 | 366.52 |
| 20 500 | 20.000 508 | 10S | 0.218 | 5.54 | 46.10 | 68.61 | 19.564 | 496.92 |
| | | 10 | 0.250 | 6.35 | 52.78 | 78.56 | 19.500 | 495.30 |
| | | STD 20 40S | 0.375 | 9.53 | 78.67 | 117.15 | 19.250 | 488.94 |
| | | XS 30 80S | 0.500 | 12.70 | 104.23 | 155.13 | 19.000 | 482.60 |
| | | 40 | 0.594 | 15.09 | 123.23 | 183.43 | 18.812 | 477.82 |
| | | 60 | 0.812 | 20.62 | 166.56 | 247.84 | 18.376 | 466.76 |
| | | 80 | 1.031 | 26.19 | 209.06 | 311.19 | 17.938 | 455.62 |
| | | 100 | 1.281 | 32.54 | 256.34 | 381.55 | 17.438 | 442.92 |
| | | 120 | 1.500 | 38.10 | 296.65 | 441.52 | 17.000 | 431.80 |
| | | 140 | 1.750 | 44.45 | 341.41 | 508.15 | 16.500 | 419.10 |
| | | 160 | 1.969 | 50.01 | 379.53 | 564.85 | 16.062 | 407.98 |
| 22 550 | 22.000 559 | 10S | 0.218 | 5.54 | 50.76 | 75.55 | 21.564 | 547.92 |
| | | 10 | 0.250 | 6.35 | 58.13 | 86.55 | 21.500 | 546.30 |
| | | STD 20 40S | 0.375 | 9.53 | 86.69 | 129.14 | 21.250 | 539.94 |
| | | XS 30 80S | 0.500 | 12.70 | 114.92 | 171.10 | 21.000 | 533.60 |
| | | 60 | 0.875 | 22.23 | 197.60 | 294.27 | 20.250 | 514.54 |
| | | 80 | 1.125 | 28.58 | 251.05 | 373.85 | 19.750 | 501.84 |
| | | 100 | 1.375 | 34.93 | 303.16 | 451.45 | 19.250 | 489.14 |
| | | 120 | 1.625 | 41.28 | 353.94 | 527.05 | 18.750 | 476.44 |
| | | 140 | 1.875 | 47.63 | 403.38 | 600.67 | 18.250 | 463.74 |
| | | 160 | 2.125 | 53.98 | 451.49 | 672.30 | 17.750 | 451.04 |

| NOMINAL PIPE SIZE | OD | SCHEDULE DESIGNATIONS | WALL THICKNESS | | WEIGHT | | ID | |
|---|---|---|---|---|---|---|---|---|
| INCH MM | INCH MM | ASME | INCH | MM | LBS/ FOOT | KG/ METER | INCH | MM |
| 24 600 | 24.000 610 | 10 10S | 0.250 | 6.35 | 63.47 | 94.53 | 23.500 | 597.30 |
| | | STD 20 40S | 0.375 | 9.53 | 94.71 | 141.12 | 23.250 | 590.94 |
| | | XS 80S | 0.500 | 12.70 | 125.61 | 187.07 | 23.000 | 584.60 |
| | | 30 | 0.562 | 14.27 | 140.81 | 209.65 | 22.876 | 581.46 |
| | | 40 | 0.688 | 17.48 | 171.45 | 255.43 | 22.624 | 575.04 |
| | | 60 | 0.969 | 24.61 | 238.57 | 355.28 | 22.062 | 560.78 |
| | | 80 | 1.219 | 30.96 | 296.86 | 442.11 | 21.562 | 548.08 |
| | | 100 | 1.531 | 38.89 | 367.74 | 547.74 | 20.938 | 532.22 |
| | | 120 | 1.812 | 46.02 | 429.79 | 640.07 | 20.376 | 517.96 |
| | | 140 | 2.062 | 52.37 | 483.57 | 720.19 | 19.876 | 505.26 |
| | | 160 | 2.344 | 59.54 | 542.64 | 808.27 | 19.312 | 490.92 |
| 26 650 | 26.000 660 | 10 | 0.312 | 7.92 | 85.68 | 127.36 | 25.376 | 644.16 |
| | | STD 40S | 0.375 | 9.53 | 102.72 | 152.88 | 25.250 | 640.94 |
| | | XS 80S | 0.500 | 12.70 | 136.30 | 202.74 | 25.000 | 634.60 |
| 28 700 | 28.000 711 | 10 | 0.312 | 7.92 | 92.35 | 137.32 | 27.376 | 695.16 |
| | | STD 40S | 0.375 | 9.53 | 110.74 | 164.86 | 27.250 | 691.94 |
| | | XS 20 80S | 0.500 | 12.70 | 146.99 | 218.71 | 27.000 | 685.60 |
| | | 30 | 0.625 | 15.88 | 182.90 | 272.23 | 26.750 | 679.24 |
| 30 750 | 30.000 762 | 10 | 0.312 | 7.92 | 99.02 | 147.29 | 29.376 | 746.16 |
| | | STD 40S | 0.375 | 9.53 | 118.76 | 176.85 | 29.250 | 742.94 |
| | | XS 20 80S | 0.500 | 12.70 | 157.68 | 234.68 | 29.000 | 736.60 |
| | | 30 | 0.625 | 15.88 | 196.26 | 292.20 | 28.750 | 730.24 |
| 32 800 | 32.000 813 | 10 | 0.312 | 7.92 | 105.69 | 157.25 | 31.376 | 797.16 |
| | | STD | 0.375 | 9.53 | 126.78 | 188.83 | 31.250 | 793.94 |
| | | XS 20 | 0.500 | 12.70 | 168.37 | 250.65 | 31.000 | 787.60 |
| | | 30 | 0.625 | 15.88 | 209.62 | 312.17 | 30.750 | 781.24 |
| | | 40 | 0.688 | 17.48 | 230.29 | 342.94 | 30.624 | 778.04 |
| 34 850 | 34.000 864 | 10 | 0.312 | 7.92 | 112.36 | 167.21 | 33.376 | 848.16 |
| | | STD | 0.375 | 9.53 | 134.79 | 200.82 | 33.250 | 844.94 |
| | | XS 20 | 0.500 | 12.70 | 179.06 | 266.63 | 33.000 | 838.60 |
| | | 30 | 0.625 | 15.88 | 222.99 | 332.14 | 32.750 | 832.24 |
| | | 40 | 0.688 | 17.48 | 245.00 | 364.92 | 32.624 | 829.04 |
| 36 900 | 36.000 914 | 10 | 0.312 | 7.92 | 119.03 | 176.97 | 35.376 | 898.16 |
| | | STD | 0.375 | 9.53 | 142.81 | 212.57 | 35.250 | 894.94 |
| | | XS | 0.500 | 12.70 | 189.75 | 282.29 | 35.000 | 888.60 |
| 42 1050 | 42.000 1067 | STD | 0.375 | 9.53 | 166.86 | 248.53 | 41.250 | 1047.94 |
| | | XS | 0.500 | 12.70 | 221.82 | 330.21 | 41.000 | 1041.60 |
| | | | 0.625 | 15.88 | 276.44 | 411.64 | 40.750 | 1035.24 |
| | | | 0.750 | 19.05 | 330.72 | 492.33 | 40.500 | 1028.90 |
| 48 1200 | 48.000 1219 | STD | 0.375 | 9.53 | 190.92 | 284.25 | 47.250 | 1199.94 |
| | | XS | 0.500 | 12.70 | 253.89 | 377.81 | 47.000 | 1193.60 |

**Note: Actual dimensions can vary from the figures based on specifications/manufacturing tolerances.**

The Data for weight is based on the following calculation for stainless steel pipe:

LB/Foot = (Outside diameter [in.] – Wall Thickness [in.]) x (Wall Thickness [in.]) x (10.69)

KG/Meter = (Outside diameter [mm] – Wall Thickness [mm]) x (Wall Thickness [mm]) x (0.0246615)